



model: TF-261

RENTAL / INDOOR 2.6 SMD 1415
 BRIGHTNESS 1000NITS
 500 x 500MM, 192x192 PX
 7KG

corners:



curve:



PARAMETER	VALUE
Pixel Pitch	2,6mm
Pixel configuration	SMD 1415
Pixel per screen module	192x192 pixels
LED type	3in1
Brightness	min. 800 cd/m ² max. 1.000 cd/m ²
Brightness control	automatic/semi-automatic/manually
Color temperature	9.500K (6500K to 9500K can be adjusted by SW)
Contrast ratio	5000:1
Viewing angle	140° H (+70°/-70°) 140° V (+70°/-70°)
Recommended viewing distance	min 2m
Input voltage	110 - 240 VAC / 50-60 Hz
Power consumption	AVG 173W/m ² MAX 520W/m ²
LED module size (cluster)	W250mmxH250mm
Screen module size	W500mmxH500mmxD73mm
Weight	7 kg/module 28 kg/m ²
Surface	0,25sqm/module
Screen module material	Die-casting alluminum
Aspect ratio	1:1
Ingress protection	IP40/IP21
Operating temperature and humidity	-20°C ~ +45°C /10% ~ 90%
Storage temperature and humidity	-40°C ~ +60°C /10% ~ 90%
Panel installation type	Front/Rear
Processing depth	14-16 bit
Control system	NOVA STAR
Colors	64 bilion
Brightness control	automatic/semi-automatic/manually

COMPANY RESIDENCE
 Screenmedia CZ s.r.o.
 Holzova 2846/21
 628 00 Brno
 Czech Republic

OFFICE
 Screenmedia CZ s.r.o.
 Holzova 10b
 628 00 Brno
 Czech Republic

CONTACT
 Phone: +420 608 18 19 20
 mail: mlcousek@screenmedia.cz
 milan@screenmedia.cz
 WWW.SCREENMEDIA.CZ