

HD29HST

Short throw HDR compatible Full HD 1080p gaming and entertainment projector





- Lights on viewing 4000 lumens
- Short throw lens 100" image from just over a metre away
- 4K UHD and HDR compatible
- Lightning-fast gaming projector Supports 1080p 120Hz with 8.4ms response time

Convenient and easy to set up, the bright and versatile HD29HST can project a 100" image from just over a metre away. It boasts HDR compatibility as well as delivering high contrast and accurate true to life colour reproduction. This compact projector is ideal for gaming, with support for 1080p 120Hz which provides a lightning-fast response time of 8.4ms. You can even use it for watching live sport, TV shows and movies.

An integrated speaker provides great sound and two HDMI inputs enable an easy setup - perfect for connecting a laptop, PC, Blu-ray player, media streamer or games console. You can even turn it into a smart projector by connecting a 4K UHD HDMI dongle like the Google Chromecast[™], Amazon Fire TV or Apple TV[™] to play games, stream videos and share photos on the big screen in the comfort of your own home.

Weighing less than 2.5kg you can take it round to a friend's house with the optional carry bag for a sports event, movie night or games marathon for a bigscreen experience anywhere with a flat surface.

Specifications

-	
Display/image	
Display technology	
Resolution	1080p Full HD (1920x1080)
Brightness	4,000 lumens
Contrast ratio	50,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	70%
Screen size	0.92m ~ 7.82m (36.2" ~ 307.8") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	0.49:1
Projection distance (m)	0.4m - 3.4m
Focal length (mm)	7.42
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	
Noise level (typical)	26dB
PC compatibility	UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security OSD / display languages	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord
	Remote control
	2x AAA batteries
	Basic user manual
	Lens cap Carry bag
Optional wireless models	WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption	0.5W
(standby)	01017
Power consumption (min)	200W
Power consumption (max)	285W
Weight and dimensions	
Net weight	3kg
Net weight	
Dimensions (W x D x H)	316 x 244 x 108



Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 02022020032404